

SKID STEER LOADERS **S550**



One Tough Animal.

Engine

Kubota / V2607-DI-T-E3B-BC-2 Make / Model Fuel Diesel Cooling Liquid Maximum power at 2700 RPM (SAE J1995) 45.5 kW Torque at 1425 RPM (SAE J1995 Gross) 201.0 Nm Number of cylinders 2600 cm³ Displacement 93.70 L Fuel tank

Weights

Operating weight 2841 kg Shipping weight 2503 kg

Controls

Vehicle steering Direction and speed controlled by two hand levers or optional Advanced Control System (ACS), Advanced Hand Controls (AHC) or Selectable Joystick Controls

(SJC)

Separate foot pedals or optional Advanced Control Loader hydraulics tilt and lift System (ACS), Advanced Hand Controls (AHC) or

Selectable Joystick Controls (SJC) Electrical switch on right-hand steering lever

Front auxiliary (standard)

Drive System

Infinitely variable tandem hydrostatic piston pumps, driving Transmission two fully reversing hydrostatic motors

Standard Features

Cushion suspension seat Automatically activated glow plugs Auxiliary hydraulics: variable flow/maximum flow Bob-Tach™ frame

Bobcat Interlock Control System (BICS)

Deluxe operator cab with windows 1 Electrically activated proportional front auxiliary hydraulics

Engine/hydraulics system shutdown

Hydraulic bucket positioning (including ON/OFF switch) Instrumentation

Lift arm support Noise reduction kit Work lights, front and rear Parking brake

Seat belt Seat bar

Spark arrestor muffler 10 x 16.5, 10-ply, Heavy duty tyres

CF certification

Warranty: 12 months or 2000 hours (whichever occurs

first)

Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

High-Flow hydraulics Deluxe instrument panel Power Bob-Tach™ Cab enclosure with heating Cab enclosure with HVAC 10 x 16.5, 10-ply, Heavy duty tyres, offset rims 10 x 16.5, 10-ply, Severe duty tyres 12 x 16.5, 12-ply, Severe duty tyres, poly filled

12 x 16.5, Solid flex tyres 31 x 12-16.5, 10-ply, Superflotation tyres Advanced Control System (ACS)

Selectable Joystick Controls (SJC) Two speed Air ride seat with 2 point seat belt Back-up alarm Beacon Engine block heater


Advanced Hand Controls (AHC)

Fire extinguisher Radio Road kit Strobe

Environmental

Fuel consumption at 100% engine load 12.90 L/min Fuel consumption at 70% engine load 10.20 L/min Fuel consumption at 50% engine load 9.10 L/min Fuel consumption at 30% engine load 7 90 I /min

Dimensions



(A)	3787.0 mm	(J)	2908.0 mm
(B)	1972.0 mm	(K)	432.0 mm
(C)	24.2°	(L)	42.0°
(D)	185.0 mm	(M)	97.0°
(E)	1082.0 mm	(N)	1727.0 mm
(F)	2657.0 mm	(O)	2032.0 mm
(G)	3378.0 mm	(P)	1374.0 mm
(H)	30.0°	(Q)	1643.0 mm
(I)	2205.0 mm		

Attachments

Angle Brooms Augers Backhoes Bale Forks **Box Blades** Breakers Brushcat™ Rotary Cutters **Brush Saws Bucket Adapters** Combination Buckets Concrete Mixers Concrete Pumps Construction / Industrial **Buckets** Diggers Dozer Blades Drop Hammers **Dumping Hoppers** Fertilizer and Grain Buckets Flail Cutters General Purpose (GP) **Bucket** Graders Grapples, Industrial Landplanes Landscape Rakes Laser Equipment Low Profile Buckets Miscellaneous Mixing Buckets Mowers Packer Wheels

Pallet Fork Accessories

Pallet Forks, Hydraulic

Pallet Forks, Standard Planers Rear Stabilizers Root Grapples Scarifiers Scrapers Seeders Skeleton Buckets Snow & Light Material Buckets Snow Blades **Snow Blowers** Snow Pushers Snow V-Blades Sod Layers Soil Conditioners Spare Wheels Spreaders Steel Tracks Stump Grinders Sweepers Tillers Tilt-Tatch Tree Transplanters **Trench Compactors** Trenchers Utility Forks Utility Frames Vibratory Rollers Water Kits Wheel Saws Whisker Brooms Wood Chippers

DOOSAN

Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2017 Bobcat Company. All Rights Reserved.

AZN9





