

SKID STEER LOADERS S650



One Tough Animal.

Engine

Bobcat / D24 Make / Model Compliancy 97/68 EC Stage IIIB Diesel Fuel Cooling Liquid Power (SAE J1995) at 2600 RPM 56.0 kW Torque at 1800 RPM (SAE J1995 Gross): 283.9 Nm Number of cylinders Displacement 2392 cm³ Fuel tank 90.50 L

Weights

Operating weight 3657 kg Shipping weight 3344 kg

Controls

Vehicle steering Direction and speed controlled by two hand levers Loader hydraulics tilt and lift Separate foot pedals, optional Advanced Control System (ACS) or Selectable Joystick Control (SJC) Front auxiliary (standard) Electrical switch on right-hand steering lever

Drive System

Infinitely variable tandem hydrostatic piston pumps, driving Transmission

two fully reversing hydrostatic motors

Turbo-charger with approved spark arrestor

Warranty: 12 months or 2000 hours (whichever occurs

Standard Features

High-back adjustable suspension seat Lift arm support Automatically activated glow plugs Work lights, front and rear Auxiliary hydraulics: variable flow/maximum flow Parking brake Bob-Tach™ frame Seat belt Bobcat Interlock Control System (BICS) Seat bar 12 x 16.5, 12-ply, Heavy duty tyres Deluxe operator cab with windows 1

Electrically activated proportional front auxiliary hydraulics

Engine/hydraulics system shutdown Hydraulic bucket positioning (including ON/OFF switch)

Instrumentation

Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options Two speed

High-Flow hydraulics Deluxe instrument panel Cab enclosure with heating Air conditioning Power Bob-Tach™ 33 x 15.5-16.5, 12-ply, Superflotation tyres, offset rims 12 x 16.5, 12-ply, Heavy duty tyres, offset rims 12 x 16.5, 12-ply, Severe duty tyres 12 x 16.5, 12-ply, Severe duty tyres, poly filled

12 x 16.5, Solid flex tyres Advanced Control System (ACS) Selectable Joystick Controls (SJC) Air ride seat with 2 point seat belt Air ride seat with 3 point seat belt Back-up alarm

Beacon Engine block heater Fire extinguisher


Strobe

CF certification

Environmental

Operator LpA(98/37 & 474-1) 85 dB(A) Noise level LWA(EU Directive 2000/14/EC) 101 dB(A) Whole body vibration (ISO 2631-1) 0.90 ms⁻² Hand-arm vibration (ISO 5349-1) 1.40 ms⁻²

Dimensions



Attachments

Angle Brooms Augers Backhoes Bale Forks Box Blades Breakers Brushcat™ Rotary Cutters Brush Saws Combination Buckets Concrete Mixers Concrete Pumps Construction / Industrial Buckets Diggers Dozer Blades Drop Hammers **Dumping Hoppers** Fertilizer and Grain Buckets Flail Cutters Forestry Cutters Graders Grapples, Industrial Landplanes Landscape Rakes Laser Equipment Low Profile Buckets Miscellaneous Mixing Buckets Packer Wheels Pallet Forks, Hydraulic Pallet Forks, Standard

Planers

Root Grapples Rotary Grinders Scarifiers Scrapers Skeleton Buckets Snow & Light Material **Buckets Snow Blades** Snow Blowers Snow Pushers Snow V-Blades Sod Layers Soil Conditioners Spare Wheels Spreaders Steel Tracks Stump Grinders Sweepers Tillers Tilt-Tatch Tree Transplanters **Trench Compactors** Trenchers Utility Forks Utility Frames Vibratory Rollers Water Kits Wheel Saws Whisker Brooms Wood Chippers

Rear Stabilizers

DOOSAN

Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2017 Bobcat Company. All Rights Reserved.

B2LA





