



Bobcat®

**COMPACT TRACK LOADERS
T590**



One Tough Animal®

T590 — SPECIFICATIONS

Machine Rating

Rated operating capacity (ISO 14397-1)	971 kg
Tipping load (ISO 14397-1)	2774 kg
Pump capacity	64.70 L/min
Pump capacity (with high flow option)	101.10 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range – optional)	16.7 km/h

Engine

Make / Model	Bobcat / D24
Compliance	97/68 EC Stage IIIB
Fuel	Diesel
Cooling	Liquid
Power	49.2 kW
Torque at 1500 RPM (SAE J1995 Gross)	245.0 Nm
Number of cylinders	4
Displacement	2392 cm ³
Fuel tank	138.20 L

Weights

Operating weight	3548 kg
Shipping weight	3187 kg

Controls

Vehicle steering	Direction and speed controlled by two hand levers or optional joysticks
Loader hydraulics tilt and lift	Separate foot pedals or optional Advanced Control System (ACS) or Selectable Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---

Standard Features

Cushion suspension seat	Noise reduction kit
Cushioned lift cylinders	Lift arm support
Automatically activated intake air heater	Work lights, front and rear
Auxiliary hydraulics: variable flow/maximum flow	Parking brake
Bob-Tach™ frame	Seat belt
Bobcat Interlock Control System (BICS)	Seat bar
Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light, electrical power port, cup holder, storage place and horn ¹	Turbo-charger with approved spark arrestor
Hydraulic bucket positioning (including ON/OFF switch)	Tracks — rubber — 320 mm
Front door with windshield wiper	CE certification
Instrumentation	Warranty: 12 months or 2000 hours, whichever occurs first

1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

Deluxe instrument panel	Air ride seat with 3 point seat belt
Power Bob-Tach™	Back-up alarm
Cab enclosure with heating	Beacon
Cab enclosure with HVAC	Strobe
High-flow auxiliary hydraulics	Radio
Air conditioning	Tracks - rubber - 400 mm
Advanced Control System (ACS)	Two speed with 3-point belt
Selectable Joystick Controls (SJC)	Road option
Radio	

Environmental

Operator LpA (98/37 & 474-1)	85 dB(A)
Noise level LWA (EU Directive 2000/14/EC)	101 dB(A)
Whole body vibration (ISO 2631-1)	0.54 ms ⁻²
Hand-arm vibration (ISO 5349-1)	1.61 ms ⁻²

Dimensions



(A) 3901.0 mm	(J) 3023.0 mm
(B) 1972.0 mm	(K) 887.0 mm
(C) 28.8°	(L) 42.0°
(D) 240.0 mm	(M) 97.0°
(E) 1402.0 mm	(N) 1727.0 mm
(F) 2657.0 mm	(N*) 1880.0 mm
(G) 3378.0 mm	(O) 2032.0 mm
(H) 30.0°	(P) 1384.0 mm
(I) 2319.0 mm	(Q) 1704.0 mm

Attachments

Angle Brooms	Pallet Forks, Standard
Augers	Planers
Backhoes	Rear Stabilizers
Bale Forks	Root Grapples
Box Blades	Rotary Grinders
Breakers	Scarifiers
Brushcat™ Rotary Cutters	Scrapers
Brush Saws	Skeleton Buckets
Combination Buckets	Snow & Light Material Buckets
Concrete Mixers	Buckets
Concrete Pumps	Snow Blowers
Construction / Industrial Buckets	Snow Pushers
Diggers	Snow V-Blades
Dozer Blades	Sod Layers
Drop Hammers	Soil Conditioners
Dumping Hoppers	Spreaders
Fertilizer and Grain Buckets	Stump Grinders
Flail Cutters	Sweepers
Graders	Tillers
Grapples, Industrial	Tilt-Tatch
Landplanes	Tree Transplanters
Landscape Rakes	Trench Compactors
Laser Equipment	Trenchers
Low Profile Buckets	Utility Forks
Mixing Buckets	Vibratory Rollers
Mowers	Water Kits
Packer Wheels	Wheel Saws
Pallet Forks, Hydraulic	Whisker Brooms
	Wood Chippers



Bobcat is a Doosan Company.

Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2017 Bobcat Company. All Rights Reserved.



Bobcat®

www.bobcat.com

